

## certoplast 102

### Structure

Highly elastic **creped paper tape** in combination with a **rubber-based adhesive** with strong tack.

### Properties

- flexible
- strong initial tack
- easy to tear
- suitable for tight curves
- can be written on
- easy to remove

### Colour

- chamois

### Applications

certoplast 102 is ideal for painting and lacquering jobs with air-drying as well as for general covering and wrapping purposes.

### Technical data

	value	dimension
backing	creped paper	
adhesive	rubber based	
thickness	0,30 ± 0,05	mm
tensile strength	≥ 20	N/cm
elongation	≥ 30	%
adhesion to steel	≥ 1,0	N/cm
temperature range (when applied)	-15 / +70	°C

### Form of supply

	value	dimension
width *	9, 12, 15, 19, 25, 30, 38, 50 ± 1,0	mm
length *	50 ± 2%	m
core *	76	mm

\* other sizes upon request



### Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

*Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.*

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

#### certoplast

Vorwerk Sohn GmbH  
Technische Klebebänder  
Müngstener Straße 100  
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0  
Fax. +49(0)202-2 55 48 48