

certoplast 105

Structure

Low creped impregnated **special paper** tape of high quality in combination with a strong **synthetic rubber-based adhesive**.

Properties

- Flexible and supple
- strong initial tack
- high temperature stability
- free of solvent
- allows the lacquering of sharp edges
- can be printed upon
- easy to remove
- also available in black colour

Colour

- chamois
- black

Application

certoplast 105 is especially suitable for oven-dried **lacquer work** and as covering for **wet-grinding applications**.

The special paper in combination with the solvent-free synthetic rubber-based adhesive allows to use the tape at many different kinds of marking- or bundling-applications.

Technical data

	value	dimension
backing	low creped, impregnated special paper	
adhesive	rubber-based	
thickness	0,15 ± 0,05	mm
tensile strength	≥ 25,0	N/cm
elongation	≥ 5	%
adhesion to steel	≥ 2,5	N/cm
temperature range (when applied)	-15 / +105	°C

Form of supply

	value	dimension
width *	9, 12, 15, 19, 25, 30, 38, 50 ± 1,0	mm
length *	50 ± 2%	m
core *	76	mm

* other sizes upon request



Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

certoplast
Vorwerk Sohn GmbH
Technische Klebebänder
Müngstener Straße 100
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0
Fax. +49(0)202-2 55 48 48