

certoplast 188

Structure

Double sided adhesive paper tape with pressure sensitive acrylate-based adhesive and covered with an paper cover.

Properties

- universal use
- high temperature resistance
- high dimensional stability
- high adhesion force
- high shear adhesion
- ageing resistant

Colour

- transparent

Application

certoplast 188 is suited for mounting screens, panels and plastic parts. It is also suitable for equipping foams and to splice papers and foils.

Technical data

	value	dimension
backing	paper	
adhesive	acrylate-based	
thickness	ca. 0,13	mm
adhesion to steel	≥ 7,0	N/cm
temperature range	-40 / +120	°C

Form of supply

	value	dimension
width *	9, 12, 15, 19, 25, 30, 38, 50 ± 1	mm
length *	50 ± 2%	m
core *	76	mm

* other sizes upon request



Recommendations for use

Fix the tape to the desired surface immediately after taking off the cover and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

certoplast

Vorwerk Sohn GmbH
Technische Klebebänder
Müngstener Straße 100
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0
Fax. +49(0)202-2 55 48 48