

## certoplast 301 Prima

### Structure

Double sided fabric adhesive tape with a strong rubber -based adhesive.

### Properties

- high adhesive force
- corresponds to VDA 0340 Typ G1
- air-permeable backing
- broad range of application

### Colour

- black

### Application

certoplast 301 Prima is especially suitable for electrical installation and repair work. It is also used for claw-care by veterinarians.

### Technical data

	value	dimension
backing	viscose fabric	
adhesive	Rubber-based	
thickness	0,3 ± 0,05	mm
tensile strength	≥ 80,0	N/cm
elongation	≥ 5	%
VDE roll	≥ 3,5	N/cm
temperature range (when applied)	-15 / +70	°C

### Form of supply

	value	dimension
width *	15, 30, 45 ± 1	mm
length *	5, 10, 25 ± 2%	m
core *	38	mm

\* other sizes upon request



### Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

*Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.*

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

#### certoplast

Vorwerk Sohn GmbH  
Technische Klebebänder  
Müngstener Straße 100  
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0  
Fax. +49(0)202-2 55 48 48