

certoplast 401

Structure

Self-fusing material from butyl rubber, in combination with an interliner.

Properties

- flexible
- waterproof
- overlapping the tape fuses at once under tensile stress
- high elongation
- permanently elastic
- easy to handle

Colour

- black

Application

certoplast 401 is especially suitable for mounting cables and cable-coupling boxes, also for repairing damaged cable-covers. Further it can be used to seal tubes and sleeves.

Technical data

	value	dimension
backing	butyl rubber / resin type	
thickness	1,0	mm
tensile strength	≥ 3,0	N/cm
dielectric strength	10	kV/mm
temperature range (when applied)	-30 / +105	°C

Form of supply

	value	dimension
width *	19 ± 1	mm
length *	5 ± 2%	m
core *	38	mm

* other sizes upon request



certoplast

Vorwerk Sohn GmbH
Technische Klebebänder
Müngstener Straße 100
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0
Fax. +49(0)202-2 55 48 48

Recommendations for use

Wrap the product with an overlapping and low elongation around the substrate. Where the material is overlapped the material will fuse slowly.

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.