

certoplast 501

Structure

Double sided adhesive tape with pressure sensitive acrylate based adhesive on fabric backing and easily removable cover.

Properties

- very high adhesive force
- high shear adhesion
- ageing resistant
- flexible fabric backing

Colour

- white

Application

certoplast 501 is especially suitable for the fastening of carpets. It is also suitable for universal use.

Technical data

| | value | dimension |
|-------------------------------------|----------------|-----------|
| backing | viscose fabric | |
| adhesive | acrylate based | |
| thickness | 0,33 ± 0,03 | mm |
| tensile strength | ≥ 25,0 | N/cm |
| elongation | ≥ 14,0 | % |
| adhesion to steel | ≥ 4,0 | N/cm |
| temperature range (when applied) | -40 / +100 | °C |

Form of supply

| | value | dimension |
|----------|-----------------------------------|-----------|
| width * | 9, 12, 15, 19, 25, 30, 38, 50 ± 1 | mm |
| length * | 25 ± 2% | m |
| core * | 76 | mm |

* other sizes upon request



Recommendations for use

Fix the tape to the desired surface immediately after taking off the cover and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

certoplast

Vorwerk Sohn GmbH
Technische Klebebänder
Müngstener Straße 100
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0
Fax. +49(0)202-2 55 48 48