

## certoplast 513

### Structure

High quality **viscose fabric tape** in combination with a strong **synthetic rubber-based adhesive**.

### Properties

- very high adhesion force
- free of critical substances
- tearable by hand
- flexible and supple
- good media resistance

### Colour

- white
- black
- grey

other colours upon request

### Application

certoplast 513 is especially suitable for the taping of cable harnesses. It has also proven useful as a bandage in veterinary applications.

### Technical data

	value	dimension
backing	viscose fabric	
adhesive	synthetic rubber -based	
thickness	0,30 ± 0,02	mm
tensile strength	≥ 80,0	N/cm
elongation	≥ 10	%
adhesion to steel	≥ 5,0	N/cm
adhesion to backing	≥ 4,5	N/cm
temperature range (when applied)	-40 / +105	°C

### Form of supply

	value	dimension
width *	15, 19, 25, 30, 38, 50 ± 1	mm
length *	50 ± 2%	m
core *	76	mm

\* other sizes upon request



### Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

*Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.*

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.