

certoplast 570

Structure

High-quality, polymer-coated viscose fabric tape in combination with a strong synthetic **rubber-based adhesive**.

Properties

- high adhesive force
- free of critical substances
- easy to tear
- closed surface
- good abrasion resistance
- resistant to ageing
- can be printed upon
- good media resistance

Colour

- black
- white
- red
- blue
- green
- yellow
- grey
- brown

Application

certoplast 570 is universally suitable for all standard requirements for repair work and fastening work and, due to its variety of colours for marking and bundling.

Technical data

	value	dimension
backing	polymer-coated fabric	
adhesive	rubber-based type	
thickness	0,28 ± 0,02	mm
tensile strength	≥ 80,0	N/cm
elongation	≥ 10	%
adhesion to steel	≥ 3,5	N/cm
adhesion to backing	≥ 3,0	N/cm
temperature range (when applied)	-40 / +120	°C
unwinding force *		
machine processing	1,0 - 3,0	N/19 mm
manual processing	3,0 - 6,0	N/19 mm

*also adjustable according to customer request

Form of supply

	value	dimension
width *	9, 15, 19, 25, 30, 38 ± 1	mm
length *	25, 50 ± 2%	m
core *	38, 76	mm

* other sizes upon request



Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.