

## certoplast 573

### Structure

High-quality PE foil, combined with a fabric inlay and a rubber-based adhesive.

### Properties

- PVC- free
- flexible and supple
- spray water repellent
- easy to tear by hand
- high adhesive force
- good media resistance

### Colours

- black
- silver-grey

### Applications

certoplast 573 serves as a standard assembly tape, eg for pipes and ventilation shafts or to attach films to metal, plastic, plaster and concrete. It can also be used for sealing against moisture.

In addition it is used in car manufacturing for the taping of cable harnesses that are exposed to moisture and spray water.

### Technical data

	value	dimension
backing	PE film with fabric	
adhesive	rubber-based	
thickness	0,18 ± 0,02	mm
tensile strength	≥ 30,0	N/cm
adhesion to steel	≥ 3,5	N/cm
adhesion to backing	≥ 3,0	N/cm
temperature range (when applied)	-20 / +80	°C

### Form of supply

	value	dimension
width *	38, 50 ± 0,5	mm
length *	50 ± 2%	m
core *	76	mm

\* other sizes upon request



### Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

*Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.*

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

#### certoplast

Vorwerk Sohn GmbH  
Technische Klebebänder  
Müngstener Straße 100  
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0  
Fax. +49(0)202-2 55 48 48