

certoplast 605

Structure

High-quality plasticised PVC foil in combination with an ageing-stable acrylate-based adhesive.

Properties

- high adhesive force
- flexible and supple
- high mechanical stability
- easy to process
- also for floor marking
- free of lead

Colour

- yellow

Application

certoplast 605 is designed for fixing foils in the building industry and to cover gaps during concrete structures.

Technical data

	value	dimension
backing	plasticised PVC foil	
adhesive	acrylate-based	
thickness	0,15 ± 0,03	mm
tensile strength	≥ 15,0	N/cm
elongation at break	≥ 125	%
adhesion to steel	≥ 1,0	N/cm
adhesion at backing	≥ 1,0	N/cm
temperature range (when applied)	-10 / +80	°C

Form of supply

	value	dimension
width *	19,25,30,38,50,100 ± 0,5	mm
length *	33 ± 2%	m
core *	38, 76	mm

* other sizes upon request



Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

certoplast

Vorwerk Sohn GmbH
Technische Klebebänder
Müngstener Straße 100
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0
Fax. +49(0)202-2 55 48 48