

certoplast 691

Structure

Plasticised PVC-foil in combination with an special acrylate-based adhesive.

Properties

- good adhesive power
- reliable protection
- lead-free
- flexible
- low restoration effect

Colour

- black

Applications

certoplast 691 is ideal for the protection of sensitive surfaces of aluminium, plastic and metal profiles.

Technical data

	value	Dimension
backing	plasticised PVC foil	
adhesive	acrylate-based	
thickness	0,15 ± 0,03	Mm
tensile strength	≥ 20,0	N/cm
elongation	≥ 190	%
adhesion to steel	≥ 1,0	N/cm
adhesion to backing	≥ 1,0	N/cm
temperature range (when applied)	-10 / +70	°C

Form of supply

	value	dimension
width *	30, 38, 50, 75, 100 ± 0,5	mm
length *	50 ± 2%	m
core *	76	mm

* other sizes upon request



Recommendations for use

Fix the tape to the desired surface immediately after unwinding and press tightly. The best results are obtained at a working temperature between 20 and 24°C.

Remark: The surface to which the tape is to be fixed must be free of oil or other contaminants such as powder, dirt or release agents. The adhesive power can be affected if the substrates contain softeners.

These details are to the best of our knowledge, nevertheless without guarantee. The suitability for special applications should first be tested by the user. The given values are statistical averages.

certoplast

Vorwerk Sohn GmbH
Technische Klebebänder
Müngstener Straße 100
D-42285 Wuppertal

Tel. +49(0)2 02-2 55 48-0
Fax. +49(0)202-2 55 48 48